

STRAPPING

PBTR REEL HOLDER REEL ROTATING WITH ROTATING TURNABLE

Applications



Construction



Paper



Cardboard



Plastic/Can



Glass



Wood

PBTR Reel holder with rotating table

The PBTR reel holder has been designed to speed up strap replacement operations. The equipment is fitted with a motorized rotating table that allows to load pallet with five different

sizes and diameters of reels and a control panel to manage operations. Pallet of coils can be loaded with forklift or manual transpallet through loading ramp (optional).

Technical data

Power supply	
Voltage	400 V (+/-10%) - 50Hz
Installed power	~ 1,1 kW


Coil data	
Max. number loadable	5
Max. load weight	600 Kg

Rotating table	
Diameter	ø 1100 mm
Rotation speed	19,8 rpm

Loading ramp for manual transpallet (Optional)

JUMBO COIL S	trap	S.JUMBO COIL	Strap
Dimensions	Meters per reel	Dimensions	Meters per reel
15,5 X 0,90	3810	19,0 X 0,85	7200
15,6 X 0,95	3700	19,0 X 0,95	6400
16,0 X 0,80	4200	19,0 X 1,00	6000
16,0 X 1,00	3400	19,0 X 1,20	5000
19,0 X 0,85	3400	25,0 X 0,80	5800
19,0 X 0,95	3000	25,0 X 1,00	4600
19,0 X 1,00	2900	25,0 X 1,27	3600
19,0 X 1,20	2400	32,0 X 1,00	3600
25,0 X 0,80	2700	32,0 X 1,27	2800
25,0 X 1,00	2200		
25,0 X 1,27	1700		
32,0 X 1,00	1700		


Standard machine dimensions



Coil size	
Type of Strap	Dimensions OD x ID x H (mm)
JUMB0	750 x 406 x 190
S.JUMBO	950 x 406 x 250

	OD
	0
Η,	ID

Pack sizes	
Strap type / Nr. of reels	Dimensions L x W x H (mm)
JUMBO / 5	750 x 750 x 1100
S.JUMBO / 4	950 x 950 x 1100 *



* Wood pallet must be adapted to be loaded (the corners must be cutted)







Detail of control panel



32,0 X 1,27

1300

Officina Meccanica Sestese S.p.A.

Via Borgomanero, 44 - 28040 Paruzzaro (NO)

www.omsspa.com

